

Date: _____
 In hands date of project: _____
 Project name/Number: _____
 Name of distributor: _____
 Client #: _____
 Name of end user: _____

ORDERING INFORMATION

Order code: 64965
 Description: LED/BR30/S2/8W/27K/STD
 UPC: 69549649651
 Case quantity: 24

PERFORMANCE DATA

Shape: BR30
 Wattage (W): 8
 Base: E26
 Lamp voltage (VAC): 120
 Colour temperature (K)**: 2 700
 Average life (L70 hours): 25 000
 Initial lumens (lm)*: 650
 Initial lumens per watt (lm/W): 81
 CRI: 84
 Beam angle (°): 105
 Power factor: 0.89
 Operating temperature range: -20 °C / -4 °F to 45 °C / 113 °F

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 5 %



This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.

CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock – do not use where directly exposed to water or weather.
- Not for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open – no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

October 20, 2016



DIMMER COMPATIBILITY LIST

Cooper	AAL06, DAL06P, SLC03P
Leviton	6615, 6674, IPE04-1LZ, IPL06
Lutron	AYCL-253P, DVELV-300P, NTELV-600, SELV-300P