

# Technical Information Bulletin

## LED Linear Tubes



Date: \_\_\_\_\_ Name of distributor: \_\_\_\_\_  
In hands date of project: \_\_\_\_\_ Client #: \_\_\_\_\_  
Project name/Number: \_\_\_\_\_ Name of end user: \_\_\_\_\_

### ORDERING INFORMATION

Order code: 65506  
Description: LED/T8/S4/9W/840/24/STD/SMX  
UPC: 69549655065  
Case quantity: 25  
DLC Unique ID: PJF8RR91



Nominal length : 48 in. (1 220 mm) Dia. : 1 1/32 in. (26 mm)

### PERFORMANCE DATA

Install method: Instant, Rapid & Program Start  
Volts (VAC): 120 V-277 V / 347 V  
Colour temperature (K)<sup>1</sup>: 4 000  
Life L70 (hrs): 50 000  
CRI: >80  
Beam angle (°) : >240  
Total Harmonic Distortion (%): <20  
Operating temperature range: -20°C to 45°F (-4°C to 113°F)

<sup>1</sup> Typical colour temperature range: +/- 5 %

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

Order code	Average System Watts (W)			Initial Lumens (lm) <sup>2</sup>		
	LBF	NBF	HBF	LBF	NBF	HBF
65506	10	12	16	1 100	1 350	1 580



Intertek  
CONFORMS TO NSF/ANSI 2

Please refer to the ballast compatibility list to confirm lamp compatibility with the existing luminaire.

### ADDITIONAL INFORMATION

THIS LAMP OPERATES ON INSTANT START, RAPID START AND MANY PROGRAM START ELECTRONIC BALLASTS.

Direct replacement for 17 watts lamps only. Risk of fire. Do not install this lamp in a pre-heat luminaire. Risk of electric shock – for use in damp locations.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: \_\_\_\_\_

Company: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.  
Data is based upon tests performed in a controlled environment and representative of relative performance.  
Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.