## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S39392**

36W/LED/HID/5000K/100-277V E26

Notes

[www] 11-22-2021 02:57:4

Compliance

| General  |   |
|--|---|
| Status   | Active  |
| Watts  | 36W   |
| Incandescent Equivalent  | 200W  |
| Fluorescent Equivalent   | 55W   |
| HID Equivalent   | 150W  |
| Volts  | 100V-277V   |
| Shape  | Corncob   |
| Base   | Medium  |
| ANSI Base  | E26   |
| Finish   | Clear   |
| CCT (Kelvin)   | 5000  |
| Temperature  | Natural Light   |
| CRI  | 80  |
| Lumens   | 5148L   |
| Beam Spread  | 300   |
| Dimmable   | Non-Dimmable  |
| Hours Rated  | 50000   |
| Lamp Type  | Corncob   |
| Technology   | LED   |
| Min Compartment Size   | Length: 8.5 in. Width: 6 in. Depth: 6 in.   |
| Ballasting Requirements  | Ballast Bypass- Direct wire only 100V-277V  |
| Electrical   |   |
|  |   |
|  | 10.00.0051/   |
| Working Voltage  | AC 90-305V  |
| Operating Frequency  | 50/60 Hz  |
| Operating Frequency Power Factor   | 50/60 Hz<br>>0.9  |
| Operating Frequency Power Factor Burning Position  | 50/60 Hz<br>>0.9<br>Universal   |
| Operating Frequency Power Factor   | 50/60 Hz<br>>0.9<br>Universal<br>Built-in surge protection - 4KV  |
| Operating Frequency Power Factor Burning Position  | 50/60 Hz<br>>0.9<br>Universal   |
| Operating Frequency Power Factor Burning Position Surge Protection   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C  |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical  | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C  |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL  | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34   |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS)  |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34   |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS)   |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Lens Material Housing Color Weight (lb.)   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS) White   |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS) White   |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Lens Material Housing Color Weight (lb.)   | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS) White   |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information                    | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS) White 1.52  UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no                  |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information                 | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS) White 1.52  UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)     |
| Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info | 50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)  7.34 3.34 Plastic (PS) Plastic (PS) White 1.52  UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes |

| Safety Listing    | cULus           |
|-------------------|-----------------|
| Location Rating   | Damp            |
| Energy Star       | No              |
| California Status | Lawful for sale |
| RoHS Compliant    | Yes             |
| FCC Compliant     | Yes             |
| SDS Sheet         | LED_Lamp        |

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







