## SATCO NUVO

Project Name

Location

Prepared By



## Notes

[www] 11-22-2021 02:57:

RoHS Compliant

FCC Compliant

General	
Status	Active
Watts	30W
Incandescent Equivalent	200W
Fluorescent Equivalent	55W
HID Equivalent	150W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish CCT (Kolvin)	Clear 5000
CCT (Kelvin)	
Temperature CRI	Natural Light 80
	4200L
Lumens  Roam Sproad	
Beam Spread  Dimmable	120;150;260 Non-Dimmable
Hours Rated	50000
	LED HID
Lamp Type Technology	LED
reciniology	Width: 8.00 in. Depth: 8.00 in.
Min Compartment Size	Height: 11.00 in.
Electrical	
Operating Frequency	50/60 Hz
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)
Operating Temperature  Physical	
Physical	(+149F)
Physical MOL	(+149F) 6.69
Physical  MOL  MOD	(+149F) 6.69 3.35
MOL MOD Lens Finish	(+149F)  6.69  3.35  Clear
Physical  MOL  MOD  Lens Finish  Lens Material	(+149F)  6.69  3.35  Clear  Thermo Plastic (PBT)
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color	(+149F) 6.69 3.35 Clear Thermo Plastic (PBT) White
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes IP64 Closed 260 deg; Partial 150 deg;
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Specification Note	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes IP64 Closed 260 deg; Partial 150 deg; Open 120 deg
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Specification Note  Warranty	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes IP64 Closed 260 deg; Partial 150 deg; Open 120 deg
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Specification Note  Warranty  Compliance	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes IP64 Closed 260 deg; Partial 150 deg; Open 120 deg 5 Year Limited - Hi-Pro
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Specification Note  Warranty  Compliance  Safety Listing	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes IP64 Closed 260 deg; Partial 150 deg; Open 120 deg 5 Year Limited - Hi-Pro
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Specification Note  Warranty  Compliance  Safety Listing  Location Rating	(+149F)  6.69 3.35 Clear Thermo Plastic (PBT) White Optional Add-On 1.37  PIR Sensor available as an accessory Yes IP64 Closed 260 deg; Partial 150 deg; Open 120 deg 5 Year Limited - Hi-Pro  CULus Classified Damp

Yes

Yes

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







