



**SKU:** SLU-25

**UPC:** 0783669828825

**Features & Benefits:**

**Description:** Copper Mechanical Lug Offset, Conductor Range 10-14, 1 Port, 1 Hole, #6 Bolt Size, UL, CSA

## Specs

### Additional Class Attributes

Collar Style	V-Bottom
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

### Dimensions

Dimension G (IN)	0.188
Dimension G (mm)	4.7752
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.661
Height BX (IN)	2.25
Height (mm)	16.7894
Length (IN)	1
Mounting Bolt/Stud Size (mm)	152.4
Mounting Hole Diameter (IN)	0.156
Mounting Hole Diameter (mm)	3.9624
Tang Length (IN)	0.469
Tang Length (mm)	11.9126
Tang Offset (IN)	0.193
Tang Offset (mm)	4.9022
Tang Thickness (IN)	0.072
Tang Thickness (mm)	1.8288
Tang Width (IN)	0.313
Tang Width (mm)	7.9502
Weight (LB)	0.012
Weight BX (LB)	2.42
Width (IN)	0.313
Width BX (IN)	5

### Material and Finish

Conductor Material	Copper
Connector Finish	NA

Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	#6
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 14 AWG = 35

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366982882

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Copper
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

**Flex Conductor Range**  
**Wire Combinations**

NA  
NA

## **Voltage**

**Voltage Rating**

35 kV