

Version: UPS 04.6(SMT) & UPS 04.3(SMC)

Applicable SKUs:

=====

ID 1015 and 1018, All standard SKUs beginning with SMT and SMC prefixes.

SMT: SMT750C, SMT750RM2UC, SMT1000C, SMT1000RM2UC, SMT1500C, SMT1500RM2UC, SMT2200C, SMT2200RM2UC, STM3000C, SMT3000RM2UC, SMT750IC, SMT705RMI2UC, SMT1000IC, SMT1000RMI2UC, SMT1500IC, SMT1500RMI2UC, SMT2200IC, SMT200RMI2UC, SMT3000IC, SMT3000RMI2UC

SMC: SMC1000C, SMC1000RM2UC, SMC1500C, SMC1500RM2UC, SMC1000IC, SMC1000I-2UC, SMC1500IC, SMC1500I-2UC

This release includes remediations for the security vulnerabilities listed as CVE-2022-22805, CVE-2022-22806 and CVE-2202-0715 which, if compromised, may allow for potential unauthorized access and control of the device.

Change logs:

1. Function implemented to disable UPS firmware upgrades via NMC to mitigate potential risk of malicious UPS firmware being passed through this channel.
2. Enhanced UPS firmware code protection to mitigate the vulnerabilities of unauthorized extraction of confidential firmware and unauthorized network access to SmartConnect UPSs.

Version: UPS 04.4

Applicable SKUs:

=====

ID 1015, All standard SKUs beginning with SMT prefixes.

SMT: SMT750C, SMT750RM2UC, SMT1000C, SMT1000RM2UC, SMT1500C, SMT1500RM2UC, SMT2200C, SMT2200RM2UC, SMT3000C, SMT3000RM2UC, SMT750IC, SMT750RMI2UC, SMT1000IC, SMT1000RMI2UC, SMT1500IC, SMT1500RMI2UC, SMT2200IC, SMT2200RMI2UC, SMT3000IC, SMT3000RMI2UC

Change logs:

1. Pre-charge control optimization on SKUs over 2.2kVA.
2. New SKUs supported .
3. Solved bug: occasionally zero run time report during battery disconnect.
4. Solved bug: "LoadShedRunTimeRemainingSetting", "LoadShedTimeOnBatterySetting" value is incorrect and unable to write from UPS (Serial & TCP/IP) Modbus
5. Solved bug: incorrect Modbus register "UPSStatusChangeCause" data when power on/off by LCD UI.

Version: UPS 04.1

Applicable SKUs:

=====

ID 1015 and 1018, All standard SKUs beginning with SMT and SMC prefixes.

SMT: SMT750C, SMT750RM2UC, SMT1000C, SMT1000RM2UC, SMT1500C, SMT1500RM2UC, SMT2200C, SMT2200RM2UC, STM3000C, SMT3000RM2UC, SMT750IC, SMT705RMI2UC, SMT1000IC, SMT1000RMI2UC, SMT1500IC, SMT1500RMI2UC, SMT2200IC, SMT200RMI2UC, SMT3000IC, SMT3000RMI2UC

SMC: SMC1000C, SMC1000RM2UC, SMC1500C, SMC1500RM2UC, SMC1000IC, SMC1000I-2UC, SMC1500I, SMC1500I-2UC

Change logs:

1. Solved the problem upper acceptable limit can't be set to 276V when output voltage setting is 240V.

2. Improved charging profile for SMT750IC and SMT750RMI2UC.
3. Added feature of Modbus over TCP, not include SMC series.
4. Fixed two report usages of USB HID on ShutdownImminent and DelayBeforeReboot. (DVT 2.2.4)
5. Implemented EnergyStar2.0/DOE function to improve efficiency based on hardware change.
6. Fixed the minimum and maximum limit for reported usages of battery run time and shutdown countdown in an application of Linux, NUT.
7. Fixed that unit did not properly show battery temperature in °F below Freezing.
8. Fixed communication lost happening frequently with PCBE.
9. RemainingTimeLimit and AudibleAlarmControl misuse mutually in USB report lufa APC asyncs.
10. Implement f/w solution to fixed the Jira issue-1145.
11. Add 125V output configuration to replace 127V.
12. Change the high line retransfer point of 125V output at poor quality.

Previous Released Version(from cloud): UPS 03.5

Version: UPS 03.5

Applicable SKUs:

=====

ID 1015 and 1018, All standard SKUs beginning with SMT and SMC prefixes.
 SMT: SMT750C, SMT750RM2UC, SMT1000C, SMT1000RM2UC, SMT1500C, SMT1500RM2UC, SMT2200C,
 SMT2200RM2UC, STM3000C, SMT3000RM2UC
 SMC: SMC1000C, SMC1000RM2UC, SMC1500C, SMC1500RM2UC, SMC1000IC, SMC1000I-2UC,
 SMC1500I, SMC1500I-2UC

Change logs:

1. Implement DOE function to improve power efficiency.
2. Improved SmartConnect cloud connectivity and ability to reconnect to the cloud over time
3. Reporting UPS events (for example: battery disconnected, output on, etc) more accurately to SmartConnect cloud server.

Previous Released Version: UPS 03.2

Applicable SKUs:

=====

ID 1015 and 1018, All standard skus beginning with SMT and SMC prefixes.
 SMT: SMT750C, SMT750RM2UC, SMT1000C, SMT1000RM2UC, SMT1500C, SMT1500RM2UC, SMT2200C,
 SMT2200RM2UC, STM3000C, SMT3000RM2UC
 SMC: SMC1000C, SMC1000RM2UC, SMC1500C, SMC1500RM2UC

Change logs:

1. Enable boost charger function.
2. Improve the battery over-temperature-protection function. The UPS will pop-up message on LCD for user to recognize.
3. Added an OEM feature - auto turn on when AC is within range.
4. Allow configuration and acknowledgement of Site Wiring Fault.
5. Added an event reporting to could when Outlet status changes.
6. Fixed reversed setting in Modbus configuration.
7. Improved a status reporting to cloud related with pending off for UPS.
8. LCD Display of runtime remaining when runtime less than one minute will report "< 1m"
9. Change default choice for confirming installation of firmware now (output on) to CONFIRMED, not CANCEL.

Initial Released Version: UPS 02.6

Applicable SKUs:

=====

SMT: SMT750C, SMT750RM2UC

Compatibility:

=====

AP9613 Dry Contact Version Next Gen Relay IO card 2.1

AP9620 LCC Version 3.0

AP9624 (Second Gen Interface Expander Card) v1.0X

AP9631/AP9630 card APP SUMX 6.2.1, AOS 6.2.1

AP9635 CH / AP9631card APP SUMX 6.4.6, AOS 6.4.6

AP9635 CH card APP SUMX 6.4.0, AOS 6.4.0

PowerChute Business Edition v9.2

FUW (Firmware Upgrade Wizard) Tool v4.1.1