

# Eaton XTOE1P6CCS

Catalog number: XTOE1P6CCS

Eaton C440 electronic overload relay, XT IEC, 0.33-1.65A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton C440 electronic overload relay	XTOE1P6CCS
<b>UPC</b>	<b>Product Length/Depth</b>
786685416458	1.77 in
<b>Product Height</b>	<b>Product Width</b>
4.33 in	1.42 in
<b>Product Weight</b>	<b>Compliances</b>
.87 lb	RoHS Compliant ATEX Compliant CE Marked

## Certifications

CSA Certified IEC 60947 EN 60947 UL Listed

## defaultTaxonomyAttributeLabel

### Frame size

45 mm

### Contact configuration

NO, NC

### Overload range

0.33-1.65A

### Type

Electronic overload relay

### Mounting method

Direct

### Trip type

Selectable 10 A, class 10 ,20, 30

## Resources

### Brochures

C440 Electronic Overload Relay

### Catalogs

Eaton's Volume 5—Motor Control and Protection

### Drawings

XTOE\_C AutoCAD 2D Footprint

XTOE\_C 3D Model Xchange

XTOE\_C AutoCAD 2D Footprint (mm)

XTOE\_C 2D PDF

XTOE\_C 2D Drawing Xchange

XTOE\_C 3D Inventor

### Installation instructions

XTOE/ZEB IEC Electronic Overload - Self Powered

### Specifications and datasheets

Eaton Specification Sheet - XTOE1P6CCS



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2022 Eaton  
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



Eaton.com/socialmedia