

Eaton XTOBP24BC1

Catalog number: XTOBP24BC1

Eaton XT IEC bimetallic overload relay, 0.16-0.24A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 7-15A contactor, 10A trip type



General specifications

Product Name	Catalog Number
Eaton XT IEC bimetallic overload relay	XTOBP24BC1
EAN	Product Length/Depth
4015082784324	3.27 in
Product Height	Product Width
1.89 in	1.77 in
Product Weight	Compliances
.3 lb	CE Marked RoHS Compliant ATEX Compliant
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Frame size

45 mm

Mounting

Direct

Overload range

0.16-0.24 A

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOB_BC1 AutoCAD 2D Footprint (mm)

XTOB_BC1 3D Model Xchange

XTOB_BC1 3D Inventor

XTOB_BC1 AutoCAD 2D Footprint

XTOB_BC1 2D Drawing Xchange

XTOB_BC1 2D PDF

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Global Data Sheet - XTOBP24BC1

Eaton Specification Sheet - XTOBP24BC1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia