

Eaton XTOB001BC1

Catalog number: XTOB001BC1

Eaton XT IEC bimetallic overload relay, 0.6-1A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 7-15A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB001BC1

EAN

4015082784355

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

.5 lb

Compliances

CE Marked RoHS Compliant ATEX Compliant

Certifications

UL Listed CSA Certified IEC 60947 EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Overload range

0.6-1 A

Type

XT IEC Bimetallic Overload Relay

Used with

7-15A contactor

Trip type

10 A

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOB_BC1 AutoCAD 2D Footprint (mm)

XTOB_BC1 3D Model Xchange

XTOB_BC1 AutoCAD 2D Footprint

XTOB_BC1 3D Inventor

XTOB_BC1 2D Drawing Xchange

XTOB_BC1 2D PDF

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Eaton Specification Sheet - XTOB001BC1

Global Data Sheet - XTOB001BC1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia