

Eaton XTOB006BC1

Catalog number: XTOB006BC1

Eaton XT IEC bimetallic overload relay, 4-6A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 7-15A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB006BC1

EAN

4015082784393

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

.7 lb

Compliances

CE Marked RoHS Compliant ATEX Compliant

Certifications

UL Listed CSA Certified IEC 60947 EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Overload range

4-6 A

Type

XT IEC Bimetallic Overload Relay

Used with

7-15A contactor

Trip type

10 A

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_BC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_BC1 2D Drawing Xchange](#)

[XTOB_BC1 3D Model Xchange](#)

[XTOB_BC1 2D PDF](#)

[XTOB_BC1 3D Inventor](#)

[XTOB_BC1 AutoCAD 2D Footprint](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Global Data Sheet - XTOB006BC1](#)

[Eaton Specification Sheet - XTOB006BC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)