

# Eaton XTOB057DC1

Catalog number: XTOB057DC1

Eaton XT IEC bimetallic overload relay, 40-57A overload range, 55 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 50-72A contactor, 10A trip type

## General specifications



### Product Name

Eaton XT IEC bimetallic overload relay

### Catalog Number

XTOB057DC1

### EAN

4015082784591

### Product Length/Depth

4.02 in

### Product Height

3.12 in

### Product Width

2.36 in

### Product Weight

.5 lb

### Compliances

CE Marked RoHS Compliant ATEX Compliant

### Certifications

UL Listed CSA Certified IEC 60947 EN 60947

### Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

## defaultTaxonomyAttributeLabel

### Frame size

55 mm

### Contact configuration

1 NO, 1 NC

### Mounting

Direct

### Overload range

40-57 A

### Type

XT IEC Bimetallic Overload Relay

### Used with

50-72A contactor

### Trip type

10 A

## Resources

### Brochures

C440 Electronic Overload Relay

### Catalogs

Eaton's Volume 5—Motor Control and Protection

### Drawings

XTOB\_DC1 AutoCAD 2D Footprint

XTOB\_DC1 3D Inventor

XTOB\_DC1 3D Model Xchange

XTOB\_DC1 2D PDF

XTOB\_DC1 2D Drawing Xchange

XTOB\_DC1 AutoCAD 2D Footprint (mm)

### Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

### Specifications and datasheets

Global Data Sheet - XTOB057DC1

Eaton Specification Sheet - XTOB057DC1



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2022 Eaton  
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



Eaton.com/socialmedia