

# Eaton XTOM2P4AC1

Catalog number: XTOM2P4AC1

Eaton XT IEC control relay, XT IEC Miniature Overload Relay, 1.6-2.4A overload range, 45 mm - mini Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, 10A trip type

## General specifications



### Product Name

Eaton XT IEC control relay

### Catalog Number

XTOM2P4AC1

### EAN

4015080144793

### Product Length/Depth

2.75 in

### Product Height

2 in

### Product Width

3 in

### Product Weight

.7 lb

### Compliances

CE Marked ATEX Compliant RoHS Compliant

### Certifications

UL Listed CSA Certified IEC 60947 EN 60947

### Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted directly to contactor.



Powering Business Worldwide

## defaultTaxonomyAttributeLabel

### Frame size

45 mm - mini

### Contact configuration

1 NO, 1 NC

### Overload range

1.6-2.4A

### Type

Control relay

### Mounting method

Direct

### Trip type

10 A

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[XTOM AutoCAD 2D Footprint](#)

[XTOM 2D PDF](#)

[XTOM 3D Model Xchange](#)

[XTOM 2D Drawing Xchange](#)

[XTOM 3D Inventor](#)

[XTOM AutoCAD 2D Footprint \(mm\)](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTOM2P4AC1](#)

[Global Data Sheet - XTOM2P4AC1](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2022 Eaton  
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)