

Project:		Type:
Drawn by:	Catalogue #:	Date:

## Individual Spec Sheet

# A19-CHOICE **LED LAMP**

#### ORDERING INFORMATION

68593 Order code:

Model number: A19/S3/9.5W/27K/ND/CHOICE/STD

UPC: 069549017610

Case quantity: 6/48

#### **PHYSICAL DATA**

A19 Shape: Base: E26

#### **PERFORMANCE DATA**

Watts (W): 9.5 Volts (VAC): 120 Colour temperature (K)1: 2 700 Average life (L70 hours)2: 15 000 Lumen output (lm)3: 922 Initial lumens per watt (Im/W): 97 CRI: 82 220 Beam angle: Power factor: 0.6

Operating temperature range: - 30 °C / - 22 °F to 40 °C / 104 °F

#### **CAUTIONS**

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock do not use where directly exposed to water or weather.
- Suitable for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Do not use with dimmers.
- For complete warranty information visit www.standardpro.com.
- 3 Years Limited Warranty.



warranty







non dimmable damp location **ICES** 005







<sup>&</sup>lt;sup>1</sup> Typical colour temperature range: +/- 5 %

<sup>2</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

<sup>3</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



### **DIMENSIONS**



Qty	Description	Price		
I accept the specifications of the luminaire configuration mentioned above.				
Name:				
Company: Signature:				
Signature:		Date:		

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

