

Q2A314N

by Burndy
Catalog ID: Q2A314N

Copper Terminal, 2 Hole, 250-350 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, 2 Screws



Product Details

General

| | |
|---------------------------------------|-------------------------|
| Connector Type | Terminal |
| Installation Torque Recommended in-lb | 325 LBS/in |
| Material | Copper |
| Physical Attribute - Number of Holes | 4 |
| Physical Attribute - Number of Screws | 2 |
| Physical Attribute - Screw Type | Hexagonal Bolt |
| Plated | N |
| Plating Type | Unplated |
| Temperature Rating | 194 |
| Trade Name | QIKLUG™ |
| Type | Bolted Lugs & Terminals |
| UPC | 781810321805 |
| UPC 12 Digit | 7818103218055 |

Dimensions

| | |
|-------------------------------------------|------------|
| Dimension - B Length inch | 1.19 in |
| Dimension - D inch | 3.09 in |
| Dimension - F Width Center to Center inch | 0.75 in |
| Dimension - Height fraction | 1-11/16 in |
| Dimension - Height inch | 1.69 in |
| Dimension - Hole Size fraction | 9/16 |
| Dimension - Hole Size inch | 0.56 in |
| Dimension - Hole Size mm | 14 mm |
| Dimension - L Length Overall mm | 114 mm |
| Dimension - Length Overall inch | 4.44 in |
| Dimension - N inch | 0.63 in |
| Dimension - Pad Width inch | 3.00 in |
| Dimension - Stud Size inch | 1/2 |
| Dimension - Width inch | 3.00 in |

Electrical Ratings

| | |
|--------------------------|-----|
| Rating - Minimum Voltage | 600 |
|--------------------------|-----|

Conductor Related

| | |
|-----------------------------------|-------------------------------|
| Conductor - Copper Str Size | 250 kcmil;300 kcmil;350 kcmil |
| Conductor - Copper Str Size Range | 250 kcmil-350 kcmil |
| Conductor Type | CU C Str-Size |

Certifications and Compliance

| | |
|-----------------------------------------|--------------|
| Certification - CSA Approved | No |
| Certification - ETL | No |
| Certification - UL Listed Direct Burial | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | EX |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 2 |
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)