



LEGRAND KEEPS THE INNOVATIONS COMING

At Legrand, we've been providing real solutions to real problems for so long, it's almost second nature. From the world's first GFCI receptacle in 1971, to the introduction of ground-breaking SafeLock* Protection some 30 years later, we've been delivering GFCI innovations designed to enhance safety, shorten installation times, and increase productivity for more than four decades.

Now, we've reset the bar on electrical safety again with our newest innovation: the P&S Self-Test GFCI Receptacle.

Designed to exceed UL requirements, it's the only GFCI that tests itself every three seconds—instead of the industry standard three hours-providing a level of reliable electrical protection that's unprecedented. The new device is also designed with a thinner profile to make more room for wires in the wall box. That means it's not only safer, but easier to install as well.

In the same way that Pass & Seymour GFCI Receptacles have been reliably protecting users for almost 40 years, they also protect the environment as well with this product line's commitment to RoHS-Compliance. RoHS (Restriction of Hazardous Substances) is a directive that requires manufacturers of certain types of electronic and electrical equipment to eliminate hazardous materials used in their products. Legrand is committed to product safety, but also our responsibility as an industry leader.







Self-Test GFCI Technology—conducts an automatic test EVERY THREE SECONDS, ensuring it's always

New external back wire pressure plates with posted terminal screws for faster installation.

Patented SafeLock® Protection:

if critical components are damaged and ground fault protection is lost, power to the receptacle is disconnected.

Enhanced tamper-resistant automatic shutter system allows for easier plug insertion while preventing young children from inserting common household objects.

Redesigned side wire cavity improves speed of side wire installation.

Now with black "invisi-shutters" for an invisible effect preferred by end users.

Meets latest UL Requirements



Ground terminal clamp allows for fast installation.

Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly.

High-impact-resistant, thermoplastic construction for superior strength and durability.

The indicator light flashes if the device fails the self-test, signaling that the GFCI should be replaced.

Auto-ground clip assures a positive ground to metal box.



2097TRW

MORE PROTECTION. MORE FUNCTIONALITY.

SAFETY IS OUR CODE

When we invented the first GFCI receptacle, our goal was to keep people safe. Today, because of their proven effectiveness, they are required by code in numerous locations. That's why we've made it our mission to offer intelligently designed solutions for every residential and commercial environment.







POWERFUL POINT-OF-USE PROTECTION

Putting GFCI protection within arm's reach means easier access for homeowners - and fewer callbacks for contractors.

Point-of-use GFCI receptacles are readily accessible and allow homeowners to spot problems quickly. GFCI breakers, however, are hidden in remote service panels in garages, basements, or other inconvenient locations. They can be challenging to access, making it difficult to restore power quickly.



RESET IT. GFCI receptacles have a trip indicator light and test/reset easily with the push of a button. Breakers, however, can be confusing and unfamiliar to homeowners, making it difficult to determine the reason for the loss of power.



PREVENT IT. Without a GFCI device that is accessible and easy to see, trips can easily go unnoticed, leading to much bigger problems. Power loss to sump pumps, freezers, or other important appliances can result in flooded basements or even more expensive property damage.



A SAFETY SOLUTION FOR EVERY HOME.



IT ALL COMES DOWN TO KEEPING PEOPLE SAFE

Our broad Pass & Seymour product line includes all the residential GFCI devices you'd expect from an industry leader—including options from our radiant® collection. In addition to stylish choices, you'll also find truly innovative solutions you need to meet special requirements, including:

Spec Grade
Tamper-Resistant
Audible Alarm
Combination Switch
Combination Night Light
Weather-Resistant

MAKE NIGHTTIME NAVIGATION AUTOMATIC.

Ideal for kitchens, bathrooms, hallways, stairs, nurseries, and more, this awardwinning device, with built-in night light, delivers advanced safety and protection.

TAMPER-RESISTANT NIGHT LIGHT/ GFCI COMBINATION

Ensures safety and convenience

- Sealed night light with Lexan® lens prevents tampering
- LED illumination with a 20+ year life expectancy means no bulbs to change
- Photocell turns night light ON in the dark—OFF in the daylight
- Performs a self-test every 3 seconds

1597NTLTRWCC4







TAMPER-RESISTANT GFCI

Helps keep children safe

- Patented shutter system—now with black "invisi-shutters" that disappear for an invisible effect—helps prevent insertion of foreign objects
- Patented SafeLock® Protection—if critical components are damaged and ground fault protection is lost, power to receptacle is disconnected
- Meets requirements
- Performs a self-test every 3 seconds
 1597TRNICC4

GFCI USB

Add charging anywhere, easily

- Exclusive functionality as the first solution on the market to combine GFCI protection and built-in charging in a single device.
- Code-approved for all areas in a remodel, as well as an ideal solution for kitchens and bathrooms in new construction.
- Adds accessible charging with two USB connections to easy, point-of-use GFCI troubleshooting for increased user convenience.
- Patented shutter system with black "invisi-shutters" for an invisible effect while preventing insertion of foreign objects.
- Performs a self-test every 3 seconds.
 1597TRUSBACW

AUDIBLE ALARM GFCI

Protection you can see and hear

- Provides an audible warning of a tripped condition and that power to a receptacle is interrupted
- Ideal for basement sump pumps and other areas where a GFCI indicator light might not be readily apparent
- Meets NEC® requirements
- Performs a self-test every 3 seconds
 1597TRAW

DECORATOR SWITCH/GFCI COMBINATION DEVICES

Ideal for remodeling

- User-preferred up-and-down switching combined with standard GFCI safety features
- Provides more functionality in
- single-gang opening
- Tamper-Resistant for added safety
- Ideal for bath and kitchen vent fans
- Performs a self-test every 3 seconds

1597SWTTRWCC4

INNOVATIONS THAT TRANSLATE INTO FASTER COMMERCIAL INSTALLATIONS



SPEED AND RELIABILITY ARE THE KEY TO SUCCESSFUL COMMERCIAL INSTALLATIONS.

Our GFCIs are designed to meet those needs...and then some. That's because we've been offering GFCIs longer than anyone else, so we know what you need to do the job right the first time. Take a look at our innovative line—we think you'll find a solution that perfectly matches your needs. Every time.

Spec Grade PlugTail®
Hospital Grade Audible Alarm
Tamper-Resistant Isolated Ground
Weather-Resistant Combinations
NAFTA-Compliant Dead Front

PLUGTAIL® GFCI

The fastest-installing GFCI ever. Hands down.

- Beats tough deadlines on any commercial job
- No exposed terminals creates a finger-safe application before, during, and after installation
- Available in Spec Grade, Hospital Grade, Tamper-Resistant, and LED/Night Light combinations
- Performs a self-test every 3 seconds
- Enables fast, affordable upgrades as space evolves

PT2097TRW





DUAL CONTROLLED GFCI

- Permanent controlled receptacle markings using abrasion resistant ink
- Controlled receptacle marking is NEMA-approved and compliant with 2017 NEC, CA Title 24 and ASHRAE Energy Efficiency Standard 90.1

2097TRCD







SPECIFICATION GRADE GFCI

- 20 amp designed for heavy commercial use
- High-impact-resistant, thermoplastic construction for superior strength and durability
- The most durable GFCI available.
 Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles
- Performs a self-test every 3 seconds 2097TRW

NAFTA-COMPLIANT GFCIS

Designed to meet government regulations

- GFCIs that meet the requirements of the Buy American provision of the American Recovery and Reinvestment Act
- Provides the same functionality and protection as our traditional GFCI
- Performs a self-test every 3 seconds

PORTABLE GFCIS

Ideal for remodeling

- Rugged polycarbonate housing stands up to impacts and hard use
- Water-resistant design for wet and corrosive indoor/outdoor environments
- Automatic reset ensures continuous power for pumps, portable signs, lights and engine heaters
- Watertight rubber cord grommets seal the GFCI from the environment 1594PC2M



Llegrand

*COLOR DESIGNATION I | Ivory

W White

G Graphite

LA Light Almond

DB Dark Bronze

O Orange

GRY Gray

BK Black

NI Nickel Brown

RED Red

Residential Self-Test GFCI Receptacles

	•				
CATALOG NO.	DESCRIPTION	RATINGS		COLORS	NEMA
		A.	V.	0020110	Config.
1597TR*	radiant* Spec Grade Tamper-Resistant 15 Amp Duplex GFCI	15	125	I, W, —, BK, LA, NI, DB, G	5-15R
1597*	radiant* Spec Grade 15 Amp Duplex GFCI	15	125	I, W, —, GRY, BK, RED, LA	5-15R
1597TRA*	radiant [®] Audible Alarm Tamper-Resistant Duplex GFCI	15	125	I, W, —, LA	5-15R
1597SWTTR*CC4	radiant® Combination Tamper-Resistant Single-Pole Switch/GFCI	15	125	I, W, BK, LA	5-15R
1597NTLTR*CC4	radiant [®] Combination Tamper-Resistant 15 Amp Night Light/GFCI	15	125	I, W, BK, LA, NI, DB	5-15R
1597TRWR*	radiant [®] Spec Grade Tamper-Resistant, Weather-Resistant 15 Amp Duplex GFCI	15	125	I, W, —, GRY, BK, LA	5-15R
1597TRR*	RoHS-Compliant radiant* Spec Grade Tamper-Resistant 15 Amp Duplex GFCI	15	125	I, W, LA	5-15R
1597TRUSBAA*	radiant* GFCI USB Outlet	15	125	I, W, -, BK, LA, NI, DB, G, GRY	5-15R
1597TRUSBAC*	radiant* GFCI USB Type-A/C Outlet	15	125	I, W, -, BK, LA, NI, DB, G, GRY	5-15R
1597TRUSBCC*	radiant* GFCI USB Type-C/C Outlet	15	125	I, W, -, BK, LA, NI, DB, G, GRY	5-15R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943, Federal Specification WC596

Commercial Self-Test GFCI Receptacles

CATALOG NO.	DESCRIPTION	RAT	INGS	COLORS	NEMA Config.
		A.	V.		
2097TR*	radiant [®] Spec Grade Tamper-Resistant 20 Amp Duplex GFCI	20	125	I, W, —, GRY, BK, RED, LA, DB, G	5-20R
2097*	radiant* Spec Grade 20 Amp Duplex GFCI	20	125	I, W, —, GRY, BK, RED, LA	5-20R
1597HGTR*	Hagnital Grade Tamper Projectont Dupley GECI	15	125	I, W, —, GRY, BK,	5-15R
2097HGTR*	Hospital Grade Tamper-Resistant Duplex GFCI	20	125	RED, LA	5-20R
1597HG*	Hospital Grade Duplex GFCI	15	125	I, W, GRY, BK, RED, LA	5-15R
2097HG*		20	125	I, W, —, GRY, BK, RED, LA	5-20R
1597IGTR*	Spec Grade Isolated Ground Tamper-Resistant	15	125	I, W, LA, O	5-15R
2097IGTR*	Duplex GFCI	20	125	I, W, GRY, LA, O	5-20R
1597IGHGTR*	Hospital Grade Isolated Ground Tamper-Resistant	15	125	0	5-15R
2097IGHGTR*	Duplex GFCI	20	125	I, W, RED, LA, O	5-20R
2097NTLTR*	radiant* Combination Tamper-Resistant 20 Amp Night Light/GFCI	20	125	I, W, GRY, LA	5-20R
2097HGNTLTR*	Hospital Grade Combination Tamper-Resistant Night Light/GFCI	20	125	I, W, GRY, RED, LA	5-20R
2097TRWR*	radiant* Spec Grade Tamper-Resistant, Weather-Resistant 20 Amp Duplex GFCI	20	125	I, W, —, GRY, BK, LA	5-20R
2097TRCD*	radiant* Spec Grade Tamper-Resistant Dual Controlled 20 Amp Duplex GFCI	20	125	I, W, —, GRY, BK, RED, LA, BL, GN	5-20R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943, Federal Specification WC596

Commercial Self-Test GFCI Receptacles

CATALOG NO.	DESCRIPTION	RATINGS		COLORS	NEMA
	DESCRIPTION	A.	V.	COLOTIO	Config
2097TRA*	radiant [®] Spec Grade Audible Alarm Tamper-Resistant 20 Amp Duplex GFCI	20	125	I, W, — LA	5-20R
1597HGTRA*	Hospital Grade Audible Alarm Tamper-Resistant Duplex GFCI	15	125	—, LA	5-15R
2097HGTRA*		20	125	I, W, RED, LA	5-20R
2097TRR*	RoHS-Compliant radiant* Spec Grade Tamper-Resistant 20 Amp Duplex GFCI	20	125	I	5-20R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943, Federal Specification WC596

Dead Front Self-Test GFCI Receptacles

CATALOG NO.	DESCRIPTION	RATI A.	NGS V.	COLORS	NEMA Config.
2087	radiant [®] Spec Grade Dead Front GFCI 1-1/2 HP Motor Control Rating	20	125	I, W, BK, LA	5-20R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943

PlugTail® Self-Test GFCl Receptacles

					ı
CATALOG NO.	DESCRIPTION	RATINGS		COLORS	NEMA
		A.	V.	OCLONO	Config.
PT1597*	Spec Grade Duplex GFCI	15	125	I, W, GRY, LA	5-15R
PT2097*		20	125	I, W, —, GRY, BK, RED, LA	5-20R
PT1597TR*	Spec Grade Tamper-Resistant Duplex GFCI	15	125	I, W, GRY, RED, LA	5-15R
PT2097TR*		20	125	I, W, —, GRY, RED, LA	5-20R
PT1597HG*	Hospital Grade Duplex GFCI	15	125	W, RED, LA	5-15R
PT2097HG*		20	125	I, W, —, GRY, BK, RED, LA	5-20R
PT1597HGTR*	Hospital Grade Tamper-Resistant Duplex GFCI	15	125	I, W, RED, LA	5-15R
PT2097HGTR*		20	125	I, W, GRY, BK, RED, LA	5-20R
PT2097NTLTR*	Spec Grade Tamper-Resistant Combination Night Light/GFCI	20	125	I, W	5-20R
PT1597HGNTLTR*	Hospital Grade Tamper-Resistant Combination Night Light/GFCI	15	125	I, RED	5-15R
PT2097HGNTLTR*		20	125	I, W, GRY, LA	5-20R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943, Federal Specification WC596





designed to be better.

designed to be better.

*COLOR DESIGNATION

Graphite

Red LA Light Almond

NI Nickel

- Brown **DB** Dark Bronze

O Orange

I | Ivory

GRY Gray

G

RED

NAFTA-Compliant Self-Test GFCI Receptacles



CATALOG NO.	DESCRIPTION	RATINGS		COLORS	NEMA
		A.	V.	0020110	Config.
1597TRNA*	NAFTA-Compliant radiant* Spec Grade Tamper-Resistant Duplex GFCI	15	125	I, W, GRY, LA	5-15R
2097TRNA*		20	125	I, W, GRY, LA	5-20R
2097NA*	NAFTA-Compliant radiant* Spec Grade 20 Amp Duplex GFCI	20	125	I, W, —, GRY, LA, BL	5-20R
2097HGTRNA*	NAFTA-Compliant Hospital Grade Tamper-Resistant 20 Amp Duplex GFCI	20	125	I, W, RED, LA	5-20R
2097HGNA*	NAFTA-Compliant Hospital Grade 20 Amp Duplex GFCI	20	125	I, W, —, GRY, RED, LA	5-20R
1597TRWRNA*	NAFTA-Compliant radiant*Tamper-Resistant Weather-Resistant Duplex GFCI	15	125	I, W, —, LA,	5-15R
2097TRWRNA*		20	125	I, W, GRY, LA	5-20R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943, Federal Specification WC596

NAFTA-Compliant PlugTail Self-Test GFCI Receptacles



CATALOG NO.	DESCRIPTION	RATINGS A. V.		COLORS	NEMA Config.
PT1597NA*	NAFTA-Compliant Spec Grade	15	125	W, GRY, LA	5-15R
PT2097NA*	Duplex GFCI	20	125	W, BK, LA	5-20R
PT2097TRNA*	NAFTA-Compliant Spec Grade Tamper-Resistant 20 Amp Duplex GFCI	20	125	I, W, LA	5-20R
PT2097HGNA*	NAFTA-Compliant Hospital Grade 20 Amp Duplex GFCI	20	125	I, W, GRY, RED	5-20R
PT2097HGTRNA*	NAFTA-Compliant Hospital Grade Tamper-Resistant 20 Amp Duplex GFCI	20	125	I, W, GRY	5-20R
PT1597NTLTRNA*	NAFTA-Compliant Spec Grade Tamper-Resistant Combination Night Light/Duplex GFCI	15	125	W	5-15R
PT2097NTLTRNA*		20	125	I, W	5-20R
PT2097HGNTLTRNA*	NAFTA-Compliant Hospital Grade Tamper- Resistant Combination Night Light/Duplex GFCI	20	125	I	5-20R

Third-Party Compliance: cULus Listed, File Number E42190, Standard UL498 & UL943, Federal Specification WC596

For additional technical or application-specific information, call 800-223-4185 or visit our website at www.legrand.us/PassandSeymour. We're eager to put our expertise to work for you.

designed to be better.



Electrical Wiring Systems 60 Woodlawn Street

West Hartford, CT 06110 1.877.BY.LEGRAND (295.3472) www.legrand.us



©2022 Legrand All Rights Reserved BR1241R4 11/22

*COLOR DESIGNATION

I | Ivory

W | White

Gray Graphite

Black

Brown Dark Bronze

Orange

Red Light Almond Nickel

GRY

BK

NI

DB

RED