

# Eaton XTCE400M22A

Catalog Number: XTCE400M22A

Eaton XT IEC contactor, 400A, 110 Vac 50 Hz, 120 Vac 60 Hz, 2NO-2NC, 400A, Frame M, 160 mm, 50-60 Hz, 125, 150, 300, 400 hp (3PH @200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton XT IEC contactor	XTCE400M22A
<b>EAN</b>	<b>Product Length/Depth</b>
4015082082093	8.50393701 in
<b>Product Height</b>	<b>Product Width</b>
7.87401575 in	6.2992126 in
<b>Product Weight</b>	<b>Compliances</b>
.5070632 lb	CE Marked RoHS Compliant
<b>Certifications</b>	<b>Catalog Notes</b>
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



## Product specifications

### Contact configuration

2 NO, 2 NC

### Coil voltage

110-120 Vac, 50/60 Hz

### Series

XT IEC

### Type

Full voltage non-reversing contactor

### HP rating - max

125, 150, 300, 400 hp (3PH @200,230,460,575 V)

### Continuous ampere rating

400 A

### Frequency rating

50-60 Hz

### Terminals

Screw terminals

### Operation

Non-reversing

### Amperage Rating

400A

### Number Of Poles

Three-pole

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[XTCE\\_M 2D Drawing Xchange](#)

[XTCE\\_M 2D PDF](#)

[XTCE\\_M 3D Model Xchange](#)

[XTCE\\_M AutoCAD 2D Footprint \(mm\)](#)

[XTCE\\_M AutoCAD 2D Footprint](#)

[XTCE\\_M 3D Inventor](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTCE400M22A](#)

[Global Data Sheet - XTCE400M22A](#)

[Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)