

Project:		Type:
		7F -
Drawn by:	Catalogue #:	Date:

## Individual Spec Sheet

# **LED REFLECTORS**

## **R20**

5 CCT Selectable

## **ORDERING INFORMATION**

Order code: 69373

Model number: R20/6.5W/5CCT/STD UPC: 069549026872

Case quantity:

## **PHYSICAL DATA**

Shape: R20 E26 Base: Heat sink color: White

#### PERFORMANCE DATA

Watts (W): 6.5 Volts (VAC): 120

Colour temperature (K)1: 2 7000/3 000/3 500/4 000/5 000

Lumen output (Im)2: 525 Efficacy (Im/W): 81 80 CRI: 25 000 Life L70 (h)3: Dimming: Phase cut Beam angle (°): 105 0.91 Power factor: Frequency (Hz): 60

Operating temp. range: -20 °C to 45 °C / -4 °F to 113 °F

Typical colour temperature range: +/- 5 %.

Limen values are derived from photometric testing. Initial lumens range: +/- 10 %.

Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

#### **LUMEN SPECIFICATION TABLE**

2 70	00 K	3 00	00 K	3 50	00 K	4 00	00 K	5 00	00 K
Lumen output (Im)	Efficacy (Im/W)								
631	97	673	103	713	110	715	110	661	102

#### COMPATIBLE DIMMERS<sup>1</sup>

Brand	Model
LUTRON	PD-5NE, PD-6WCL, DVCL-153P, CTCL-153P, DVCL-253P, DVRP-253-WH, SELV-300P, MACL-153P
COOPER	RRD-6NA-WH, AAL06, SLC03P
LEVITON	IPL06, 6674, DSL06-1ZL, DSM10-1LZ, DDMX1
LEGRAND	RH703PTUTC

<sup>1</sup> This table shows dimmers that have been tested and have demonstrated proper operation under Initiatable shows diminifest that have been tested and nave demonstrateal proper operation under normal conditions. Each installation being unique, various factors such as load, common neutral or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. Standard recommends to use dimmers disagned to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

### **DIMENSIONS**





























