

BG24 Flexible Copper Braid

By Burndy Catalog # BG24

Cu Flexible Braid Jumper, 2 Holes 2 Ferrules, 1.50" Spacing, 24.00" L, .44" Hole Dia., Amp Rating: 415 (Indoor) 495 (Outdoor)



Application

Flexible Copper braid jumpers designed to take up linear expansion and contraction, compensate for misalignment and absorb vibratory movement of electrical equipment and devices

General

Connector Type Braid Construction Material - Main Copper EU RoHS Indicator Yes Material Copper Material - Ferrules Physical Attribute - Number of 1 **Braids** Plated Sub Brand Braid TYPE B Туре 781810005149 UPC

UPC 12 Digit **Dimensions**

Dimension - D inch 3.00 in Dimension - Hole Size inch 0.44 in Dimension - L Length Overall 610 mm mm Dimension - Length Overall 24.00 in inch Dimension - N inch 0.75 in Dimension - Pad Width inch 1.50 in 24 in Lenath

Electrical Ratings

Rating - Indoor Amperage 415 A Rating - Outdoor Amperage 495 A

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

3D Models - BG24_MODEL-STEP 3D Models - BG24_MODEL-PDF 3D Models - BG24_MODEL-IGES Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SE..210201-01



7818100051499