

HRD SNOW SENSOR



nVent RAYCHEM HRD Snow Sensor accurately detects falling or blowing snow as precipitation at temperatures below 38 °F/3.3 °C for surface snow melting applications. Typically the CIT-1 aerial sensor is paired with either the GIT-1 sensor for gutter applications or the SIT-6E sensor for pavement applications.

FEATURES

- Simple and fast to install
- Excellent snow detection accuracy, using precision precipitation and temperature sensors
- Aerial snow sensor detects falling or blowing precipitation before snow or ice begin to accumulate
- No ice bridging, due to the unique microcontroller design
- Remote use, with up to 2000 ft/609.6 m separation from the control panel possible
- Reliable during long life: 10 year product warranty available, maintenance free

SPECIFICATIONS

Supply Voltage: 24 V
IP Rating: IP67

Table 1/1

Catalog Number	Item Name	Sensor Type	Height	Width	Depth
126795-000	HRD-GIT-1-GUTTER-SENSOR	Gutter	38.1 mm	141.2 mm	38.1 mm
P000000112	SIT-6E	Pavement	102 mm	99 mm	99 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258

Fax +1.800.527.5703

thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511

Fax +32.16.213.604

thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688

Fax +86.21.5426.3167

cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800

Fax +1.713.868.2333

thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER