

12 VDC, 3 A Power Adapter



- Supports 90 VAC to 264 VAC Wide-range Voltage Input
- Meets the Demands of Voltage Fluctuation
- 4KV Outdoor Lightning Protection

Technical Specification

Electrical

Input Voltage	90 VAC to 264 VAC, 50/60 Hz
Output Voltage	12 VDC (+7%, -3%)
Output Current	3 A
Maximum Power Output	36 W
No Load Power Consumption	< 0.3 W

Protection

Protections	Surge protection Over temperature Over current Voltage load
ESD	IEC61000-4-2 ±6 kV Contact; ±8 kV Air
Surge	Surge: EN61000-4-5 Combination Wave: Common Mode ±4kV (12 Ω) Differential Mode ±2kV (2 Ω)

Environmental

Operating Temperature	-10° C to +55° F (14° F to 131° F)
Operating Humidity	< 90%, Relative

Physical Properties

Dimensions (L x W x H)	101.50 mm x 51.10 mm x 55.60 mm (4.0 in. x 2.01 in. x 2.19 in.)
Weight	0.17 kg (0.38 lb)
Installation Mode	Wall-mount
Color	Black
Input Plug	2-pin North American Plug
Outgoing Cord	DC wire: 1500.0 mm (59.06 in.)
DC Plug	∅5.50 mm x ∅2.10 mm x 10.0 mm (∅0.22 in. x ∅0.08 in. x 0.39 in.)

Certifications

Safety	UL
--------	----

Dimensions

