Eaton E51BLT16PU

Catalog Number: E51BLT16PU

Eaton E51 NEMA limit switch inductive proximity sensor, Factory Sealed 6P+ Inductive Proximity Top Sensor Enclosure, 2-Wire AC, NC, 500 mA AC/DC SS Output, 8 Ft.(2.5m) Cable, 20-264Vac/DC input, < 0.3% accuracy, Shielded, 8 Ft.(2.4m)

General specifications



Product Name Catalog Number
Eaton E51 NEMA limit switch inductive E51BLT16PU

proximity sensor

UPC

782113866154

Product Length/Depth Product Height

1.54 in 4.96 in

Product Width Product Weight

1.58 in 1.1313 lb

Warranty Certifications

1 year UL Listed

CSA Certified

Catalog Notes

Sensor head is hard wired to sensor body and cannot be detached; but can be unfastened and rotated to any of four positions.



defaultTaxonomyAttributeLabel

Contact Rating

500 mA AC/DC Solid State Output

Actuator function

Shielded

Cable type

SOOW-A

Accuracy

< 0.3%

Enclosure material

Housing: die cast zinc

Head: plastic

Connection

8 ft (2.4 m) cable

Contact configuration

2-wire AC, NC

Sensor type

Inductive proximity

Environmental rating

NEMA 3, NEMA 3S, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P,

NEMA 12, NEMA 13, IP68

Cord length

8 ft

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Maximum AC current

500 mA

Maximum DC current

500 mA

Input voltage

20-264 Vac/dc

LED indicator

Power on: green
Output status: yellow

Resources

Catalogs

Eaton's Volume 8—Sensing Solutions

Specifications and datasheets

Eaton Specification Sheet - E51BLT16PU

Protection

Short circuit protected



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia