

# Eaton M22-D-R-GB0

Catalog Number: M22-D-R-GB0

Eaton 22.5 mm RMQ-Titan Pushbutton, STOP, Red Actuator, Silver bezel, IP67, IP69K, Non-illuminated, Flush mounting, NEMA 4X, 13,5,000,000 operations, Momentary, 22.5 mm, Flush Pushbutton, M22



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton M22 modular pushbutton	M22-D-R-GB0
<b>UPC</b>	<b>Product Length/Depth</b>
786685276366	7 in
<b>Product Height</b>	<b>Product Width</b>
1.5 in	5 in
<b>Product Weight</b>	<b>Warranty</b>
1 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>Compliances</b>	<b>Certifications</b>
CE Marked GoST-R Bureau Veritas	CCC Marked CSA Certified Lloyd's Register Certified

## Catalog Notes

Includes contact block mounting adapter.

## defaultTaxonomyAttributeLabel

### Type

Pushbutton

### Actuator color

Red

### Bezel

Silver

### Actuator function

Momentary

### Enclosure

IP67

IP69K

### Button color

Red

### Actuator

Flush, button

### Operating mode

Momentary

### Illumination

Non-illuminated

### Series

M22

### Environmental rating

IP67, IP69K, NEMA 4X, NEMA 13

### Etching code

STOP

### Operating cycles

5 million

### Mounting method

Flush

### Degree of protection

NEMA 13

NEMA 4X

### Inscription

STOP

### Product category

## Resources

### Brochures

[M22 Pilot Devices](#)

### Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

### Installation instructions

[M22 Operators and Accessories](#)

### Specifications and datasheets

[Global Data Sheet - M22-D-R-GB0](#)

[Eaton Specification Sheet - M22-D-R-GB0](#)

Flush pushbutton

Size

22.5 mm



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)