

ONE SUPERIOR FAN WITH ENDLESS POSSIBILITIES

The ideal IAQ solution for virtually any space

For over two decades, Panasonic has developed innovative solutions that promote better indoor air quality and healthy home building. On our mission to help you build healthy homes, WhisperGreen® Select offers a powerful customizable IAQ solution that delivers healthy indoor air quality for healthy living in any space.

Although ASHRAE, ENERGY STAR®, LEED for Homes, and HVI have set the industry standard for performance measurement at 0.1" and 0.25", Panasonic has yet again found a way to stay ahead of the game. WhisperGreen® Select fans provide superior installed performance and powerful CFM output up to 0.5"

WHISPERGREEN® SELECT IS AS EASY AS 1-2-3!

Step 1- Select a Base Fan Model

Select a base model to start building the perfect IAQ solution that satisfies your ventilation design requirements.

Pick-A-Flow® Airflow Technology

Pick-A-Flow® Airflow Selector – one fan, you choose the CFM. Provides the unique ability to select your required airflow (50-80-110 and 110-130-150 CFM models) with the simple flip of a switch.

Fan Only	Fan/Light
FV-0511VK3- 50-80-110 CFM Pick-A-Flow® single speed	FV-0511VKL3- 50-80-110 CFM Pick-A-Flow® single speed + LED Light
FV-0511VKS3- 30 to 110 CFM pre-installed multi-speed	FV-0511VKSL3- 30 to 110 CFM pre-installed multi-speed + LED Light
FV-1115VK3- 110-130-150 CFM Pick-A-Flow® single speed	FV-1115VKL3- 110-130-150 CFM Pick-A-Flow® single speed + LED Light
FV-0511VKS3S- 30 to 110 CFM pre-installed multi-speed	FV-0511VKSL3K- 30 to 110 CFM pre installed multi-speed + LED Light


Step 2- Select Value Added Features

WhisperGreen® Select offers a unique set of five patented modules that allow you to further customize your fan.



Wi-Fi Module (WP100PBA)

Enables two-way wireless communication between ventilation products. Easily connect, monitor and control the fan's features (ie. motion sensor, light, etc.) with the Swidget™ app. The Wi-Fi module can operate with a standalone fan, or can be used as part of an Indoor Air Quality healthy home system.



Smart Action® Motion Sensor + Condensation Sensor (FV-CMVK3)

Automatically activates the fan when someone enters the room, or when relative humidity and temperature are about to reach dew point, automatically turning on the fan to control humidity.



Multi-Speed with Time Delay (FV-VS15VK1)

Allows you to select the proper CFM settings to satisfy ASHRAE 62.2 continuous ventilation requirements. The fan runs continuously at a pre-set lower level, then elevates to a maximum level of operation when the wall switch is turned on, or when the SmartAction® motion sensor or condensation sensor module is activated. A high/low delay timer returns the fan to the pre-set CFM level after a period of time set by the user.



SmartAction® Motion Sensor (FV-MSVK1)

Automatically activates when someone enters the room. Once the settings have been applied, the fan becomes truly automatic, making it ideal for people with disabilities and assisted living environments such as nursing homes and retirement communities. This module also activates an automatic 20-minute delay off timer for the fan.



Condensation Sensor (FV-CSVK1)

Helps control bathroom condensation to prevent mold and mildew. Advanced sensor technology detects relative humidity and temperature to anticipate dew point, automatically turning the fan on to extract humidity. Built-in Relative Humidity (RH) sensitivity adjustment enables fine tuning for moist conditions (30% to 80%, in 10% increments) and for satisfying CALGreen requirements. When the condensation sensor is used in conjunction with multi-speed functionality, the fan will kick up to high speed when the condensation sensor detects moisture in the room. This module also activates an automatic 20-minute delay off timer for the fan.

Step 3- Install Your Ideal Fan with the Flex-Z Fast® Installation System

Ingeniously designed installation bracket provides flexible, fast and easy installation for all your new construction or renovation projects.



Single-hinged articulating joints to easily position bracket in between the joist and/or through ceiling hole.



Easily position bracket in between the joist or ceiling hole.



Extend bracket to desired length.

LED Lighting

JA-8 compliant for CA Title 24/50,000 hours rated average life. Standard fan/light models feature a warm white LED light. All Architectural models feature a five Color Changing Temperature LED light.