## Data Sheet | Item Number: 2006-403 Jumper; 3-way; insulated; light gray

https://www.wago.com/2006-403





Color: ■ light gray

Electrical data			
Ratings per IEC/EN		Ex information	
Nominal voltage (III/3)	800 V	Rated current (Ex e II)	33 A
Rated current	41 A		

Physical data		
Width	20.2 mm / 0.795 inches	
Height	4.1 mm / 0.161 inches	
Depth	19 mm / 0.748 inches	
Jumper assignment	1-2-3	

Material data	
Note (material data)	
	<u>Information on material specifications can be found here</u>
Color	light gray
Fire load	0.013 MJ
Weight	3.2 g

weigni		5.2 y	
Environmental requirements			
Environmental Testing (Environme	ntal Conditions)	Environmental Testing (Environme	ntal Conditions)
Test specification Railway applications – Rolling stock – Electronic equipment	DIN EN 50155 (VDE 0115-200):2022-06	Acceleration	0.101g (highest test level used for all axes) 0.572g (highest test level used for all axes)
Test procedure Railway applications – Rolling stock equipment –	DIN EN 61373 (VDE 0115-0106):2011-04	Test duration per axis	5g (highest test level used for all axes) 10 min. 5 h
Shock and vibration tests Spectrum/Installation location	Service life test, Category 1, Class A/B	Test directions	X, Y and Z axes X, Y and Z axes X, Y and Z axes
Function test with noise-like vibration	Test passed according to Section 8 of the standard	Monitoring for contact faults/interrupti-	Passed
Frequency	$f_1 = 5 \text{ Hz to } f_2 = 150 \text{ Hz}$ $f_1 = 5 \text{ Hz to } f_2 = 150 \text{ Hz}$	ons  Voltage drop measurement before and after each axis	Passed
		Simulated service life test through increased levels of noise-like vibration	Test passed according to Section 9 of the standard

## Data Sheet | Item Number: 2006-403

https://www.wago.com/2006-403



Environmental Testing (Environmental Conditions)		
Extended test scope: Monitoring for contact faults/interruptions	Passed Passed	
Extended test scope: Voltage drop measurement before and after each axis	Passed Passed	
Shock test	Test passed according to Section 10 of the standard	
Shock form	Half sine	
Shock duration	30 ms	
Number of shocks per axis	3 pos. und 3 neg.	
Vibration and shock stress for rolling stock equipment	Passed	

Commercial data	
Product Group	22 (TOPJOB S)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 8.0	EC000489
PU (SPU)	25 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143701372
Customs tariff number	85366990990

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

Page 2/2 Version 28.03.2025