



Color: ■ light gray

Electrical data

| Ratings per IEC/EN                        |       |
|---|-------|
| Nominal voltage (III/3)                   | 800 V |
| Rated impulse withstand voltage (III / 3) | 8 kV  |
| Rated current                             | 25 A  |

Physical data

|                   |                        |
|-------------------|------------------------|
| Width             | 10.9 mm / 0.429 inches |
| Height            | 4.1 mm / 0.161 inches  |
| Depth             | 18.5 mm / 0.728 inches |
| Jumper assignment | 1-4                    |

Material data

|                      |  |
|----------------------|--|
| Note (material data) | <a href="#">Information on material specifications can be found here</a> |
| Color                | light gray   |
| Fire load            | 0.012 MJ   |
| Weight               | 1.1 g  |

Commercial data

|                       |               |
|-----------------------|---------------|
| PU (SPU)              | 25 pcs        |
| Packaging type        | Bag           |
| Country of origin     | DE            |
| GTIN                  | 4066966320220 |
| Customs tariff number | 85366990990   |



| Product classification |  |          |
|------------------------|--|----------|
| UNSPSC                 |  | 39121421 |

| Environmental Product Compliance |  |                        |
|----------------------------------|--|------------------------|
| RoHS Compliance Status           |  | Compliant,No Exemption |

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2002-424

↓

CAD/CAE-Data


CAD data

2D/3D Models 2002-424

↓


Installation Notes

Commoning



The 1-to-3 adjacent jumper for continuous commoning enables every other terminal block to be commoned. For example, positive and negative potentials can be accommodated alongside each other.

Commoning



By combining a 1-to-2 continuous jumper with a 1-to-3 adjacent jumper, various commoning applications can be performed in just one jumper slot.