


Nonmetallic - Cable tray

Splice plates

01 6" (152.4mm)
Splice plate (comes with
nonmetallic hardware)




01

Splice plate number selection

- Example:**
NM-XSS4004SS6
- 316 stainless steel
 - 4 holes supplied with 316 stainless steel hardware for a 4" (101.6mm) deep straight section.

NOTE: Splice plates shown on pages B38-B41 represent splices for 6" (152.4mm) side rail height. Number of holes may vary with other side rail heights.



1 : 4 holes for series 3 and 4 only. 8 holes for series 6 and 8 only.
2 : Only noted for angled splice plates, do not include for straight, expansion and adjustable splice plates.
3 : Minimum order quantity of 7 is required.

Nonmetallic - Cable tray

Splice plates

Standard splice plates

	Cat. No.	Material	Height (in.)	Height (mm)
	NM-XSS-8008*	Stainless steel Polyester resin Vinylester resin	8	203.2
	NM-XSS-8006*		6	152.4
	NM-XSS-4004*		4	101.6
	NM-XSS-4003*		3	76.2

* Hardware suffix needed to complete catalog number. All splice plate hardware is 3/8". Quantity required supplied with each tray section. Order only pairs of splice plates needed for field modifications. SS6 hardware supplied as standard - use SS6 suffix. Other hardware available; specify by hardware suffix.

Expansion splice plates

	Cat. No.	Material	Height (in.)	Height (mm)
	NM-XSS-8018*	Stainless steel Polyester resin Vinylester resin	8	203.2
	NM-XSS-8016*		6	152.4
	NM-XSS-4014*		4	101.6
	NM-XSS-4013*		3	76.2

Allow for up to 1" (25.4mm) expansion or contraction of tray system. For correct gap setting procedure, see page B10.

* Hardware suffix needed to complete catalog number.

Horizontal adjustable splice plates

	Cat. No.	Material	Height (in.)	Height (mm)
	NM-XSS-8038*	Stainless steel Polyester resin Vinylester resin	8	203.2
	NM-XSS-8036*		6	152.4
	NM-XSS-4034*		4	101.6
	NM-XSS-4033*		3	76.2

Provide for changes in the horizontal direction that do not conform to standard fittings. Furnished in pairs.

* Hardware suffix needed to complete catalog number.

Vertical adjustable splice plates

	Cat. No.	Material	Height (in.)	Height (mm)
	NM-XSS-8028*	Stainless steel Polyester resin Vinylester resin	8	203.2
	NM-XSS-8026*		6	152.4
	NM-XSS-4024*		4	101.6
	NM-XSS-4023*		3	76.2

Provide for changes in elevation that do not conform to standard vertical fittings. Furnished in pairs.

* Hardware suffix needed to complete catalog number.