

| Product Code | Alt Code | Size |
|--------------|----------|------|
| 129092       | 902036W  | 2"   |

## SUPER<sup>®</sup> DUCT

Power & Communication Duct



### APPLICATION / USE:

- Concrete encased and direct burial applications for power utilities
- street lighting and communication distribution systems

### CERTIFICATIONS

- CSA C22.2 No. 211.1

Super Duct DBII 90° duct elbows come with bell ends, and are specially formulated from a high impact PVC and comply with NEMA TC-9 Standard.

### FEATURES

- Lightweight
- Bell-ended to allow for easy assembly in the field
- High compressive strength
- Low coefficient of friction
- Manufactured with a specialized compound
- Engineered for high impact and crush strength specifically required by utilities for underground duct
- Specialized compound enhances the friction coefficient of Super Duct for easier pulling of conductors/wires through long runs
- Conforms to the testing requirements of CSA standard C22.2 No. 211.1 both for encasement in concrete masonry and for direct burial.
- High-impact and crush strength demanded by today's utility companies for underground applications
- Easy to assemble
- Conforms to the requirements of CSA Standard C22.2 No. 211.1 for encasement in concrete and direct burial.



ipexna.com

© 2024 IPEX

Product is manufactured by IPEX Electrical Inc.

